



## **PRO** SERIES

## **Gas-Powered**

## **Pulling Winch GXH50**



SINGLE LINE PULLING FORCE 2,200 LB



DOUBLE LINE PULLING FORCE **4,400 LB** 



WINCH TILT



+/- 20°



SPEED

MAX 40'/MIN



WEIGHT

35 LB



**POWER** 

1.6 kW | 2.1 HP



MOTORIZATION

**HONDA 4-STOKE GXH50** 



POWERED BY

GAS



PRIVATE USE WARRANTY **5 YEARS** 



	PCW5000
Series	Pro
Designed in	2003
Motor/Engine	HONDA HONDA HONDA GARAGO HONDA HONDA HONDA GARAGO HONDA HONDA GARAGO HONDA HON
Powered by	Gas
Drive/Clutch	Direct drive (no clutch)
Rope Retention System	No
Drum turns when motor/engine is idling	Yes
Pulling Capacity	
Standard drum (single line / double line)	Ø 2-1/4" (57 mm): 2,200 lb / 4,400 lb
Optional drum (single line / double line)	Ø 3-3/8" (85 mm): 1,600 lb / 3,200 lb
Lifting Capacity	
Standard drum (single line / double line)	Not designed for lifting - See INDUSTRIAL SERIES winches
Optional drum (single line / double line)	
Speed	
Standard drum	Ø 2-1/4" (57 mm): 40"/min
Optional drum	Ø 3-3/8" (85 mm): 60'/min
Weight	35 lb
Dimensions (overall)	14-5/8" x 14-3/8" x 14-3/8"
Gearbox	Aluminium alloy. Heat treated 3-stage spur gears.  Mounted on ball bearings. Oil bath lubrication.
Gear ratio	110:1
Brake	Anti-reversing roller clutch bearing Low stretch double braided polyester
Rope (not included) Length	Unlimited
Minimum diameter	Ø 3/8" (10 mm)
Maximum diameter	Ø 1/2" (13 mm)
Recommended diameter	Ø 1/2" (12 mm)
Included	Polyester sling - 2-1/2" x 6-1/2"
Warranty	Get 1 additional year of warranty if you register your product at www.portablewinch.com
Private use	5 years
Commercial use	1 year
Motor/Engine	Honda International Warranty
Certification	C€